

EUROPEAN PATENT APPLICATION

Application number: **85106717.3**

Int. Cl.: **G 01 N 30/74, G 01 N 21/03**

Date of filing: **31.05.85**

Priority: **08.06.84 US 617700**

Applicant: **ISCO, Inc., 4700 Superior Street, Lincoln Nebraska 68504 (US)**

Date of publication of application: **11.12.85 Bulletin 85/50**


Inventor: **Allington, Robert William, 2030 Euclid, Lincoln Nebraska 68502 (US)**

Designated Contracting States: **DE FR GB**

Representative: **UEXKÖLL & STOLBERG Patentanwälte, Beeselerstrasse 4, D-2000 Hamburg 52 (DE)**

Method and apparatus for reducing schlieren noise in a liquid chromatograph.

A beam of light falling within the range of 180 to 3,000 nanometers is transmitted through a flow cell (12) in an optical compartment of an absorbance detector (16) after warm up of the equipment while the eluant flows through the flow cell (12) from a chromatographic column (20). The column extends upwardly from the absorbance detector (16) into an air chamber (60) having a volume of approximately 0.25 cubic foot formed with acrylic walls. Air flows from the absorbance detector (16) under the power of a fan at approximately 10 cubic feet per minute upwardly through an air duct having a cross section of approximately 1.5 square inches to the top where it connects with the air chamber (60), the speed of the motor being adjustable until temperature varies less than one degree Celsius between the flow cell (12) and the lower 10 centimeters of the column. Under these conditions Schlieren noise from the flow cell (12) due to flow-induced thermo-optical effects is reduced.



EP 0 164 080 A2

METHOD AND APPARATUS FOR REDUCING SCHLIEREN NOISE
IN A LIQUID CHROMATOGRAPH

This invention relates to methods and apparatus for reducing Schlieren noise in a liquid chromatograph.

It is known to reduce Schlieren noise in a liquid chromatograph by reducing the temperature differences between the eluate and the flow cell. This reduces the difference in density and hence differences in refraction index between portions of the eluate in the flow cell. Since the eluate is in motion, such differences deflect light in an unpredictable manner, thus producing photometric noise.

The prior art technique attempts to maintain a temperature equality between the flow cell and the eluate entering the flow cell by introducing the eluate into a heat exchanger built into the flow cell. In this technique, the outlet of the heat exchanger is connected to the flow entrance of the flow cell and the body of the heat exchanger is thermally connected to the body of the flow cell. Another technique is to use a conical optical path in the flow cell so that Schlieren scattered light is not absorbed by the cell walls.

The prior art techniques have several disadvantages, such as: (1) a substantial amount of Schlieren noise remains; (2) the absorbance detector causes heat

to be conducted to the flow cell and therefore sets up temperature gradients within the flow cell with respect to the flow of eluate; (3) the techniques are slow to stabilize and require much time before measurements can be made without excessive Schlieren noise; and (4) the fluid volume of the heat exchanger or the excess volume of the conical optical path over a cylindrical path degrades the degree of separation of narrow chromatographic peaks or bands in the eluate.

10 The disadvantage caused by the fluid volume of the heat exchanger or the excess volume of the conical optical path over a cylindrical path is a particular problem with micro-liquid chromatography. A common column diameter for micro-liquid chromatography (MLC) is one millimeter and a common conventional high performance liquid chromatography (HPLC) column diameter is 4.6 millimeters. Thus, the cross sectional area of a MLC column is about one-twentieth ($1/20$) that of an HPLC column, and so MLC solute peaks are smaller in volume by
20 at least a factor of 20. It is more than a factor of 20 if the length of a peak residing in the column also decreases when going from HPLC to MLC.

 Because the solute peaks are smaller in MLC, the peak resolution degradation problems are aggravated because of the difficulty of detecting and collecting

low volume bands. This problem is further aggravated when micro-capillary MLC columns with a diameter of 0.1 millimeter or less are used.

10 The smaller peak volumes of MLC require proportionately smaller fluid volumes in the optical path in order to maintain the same chromatographic resolution. Since shortening the optical path length decreases the absorbance sensitivity according to Beer's Law, the diameter of the path length must be made smaller instead. The greater length to diameter ratio of MLC cells increases their Schlieren noise over that of comparable HPLC cells, thus making it even more of a problem with MLC than with HPLC. The conventional HPLC noise reduction methods are undesirable for MLC because they degrade volumetric resolution which is much more critical for MLC than for HPLC.

20 Accordingly, it is a task of this invention to provide a novel method for operating a liquid chromatograph which reduces Schlieren noise by reducing the temperature in the vicinity of the flow cell.

There is provided a method of operating a liquid chromatograph having at least a chromatographic column, a sample injection valve, and a flow cell. In this method electrical power is applied to an absorbance

detector within an enclosure containing at least the flow cell and a portion of the chromatographic column and is caused air to flow from the enclosure into an air chamber that encloses a sample injection valve and at least a part of a chromatographic column.

10 The air is recirculated from a location near the sample injection valve along the column toward the flow cell until temperature changes with respect to time at each location are within less than 0.1 degree Celsius within the enclosure and chamber within a one minute time period. After the temperature has stabilized through the column and flow cell, a beam of light having a wave length within a range of wave lengths of 180 nanometers to 3,000 nanometers is transmitted through the flow cell from a source of light that varies less than ten percent in intensity in a one minute period; and detecting changes in the absorbance of light through said flow cell with the air flow being caused initially by blowing air from the enclosure to the inlet of the chromatographic column and back to the enclosure at a rate in the range of 1 to 100 volumes of air per minute for each volume of capacity of the chamber. The blowing of air is discontinued after the temperature has stabilized and it is permitted to flow at a rate of at least .001 volume of air per minute for each volume of

20

capacity of the air chamber.

Advantageously, the air flows along a chromatographic column from an electro-optical enclosure and back to the enclosure in the same direction the eluant flows in the column and, after temperature has stabilized with respect to time in the enclosure, performing chromatographic runs air flows from the enclosure into the air chamber having at least a part of a chromatographic column within it and is recirculated
10 from a point on the column spaced away from its end closer to the flow cell into juxtaposition with the flow cell until the temperature has stabilized within the air chamber.

The above noted and other features of the invention will be better understood from the following detailed description when considered in connection with the accompanying drawings, which are:

FIG. 1 is a fragmentary simplified perspective view in accordance with an embodiment of the invention;

20 FIG. 2 is a schematic showing of a portion of the embodiment of FIG. 1; and

FIG. 3 is a partly broken-away, perspective view of the embodiment of the invention of FIG. 1 from another angle.

10 In FIG. 1, there is shown a simplified perspective view of an apparatus 10 for reducing Schlieren noise in a liquid chromatograph having a flow cell assembly 12, a light path assembly 14, an electro-optical section 16 and an air flow control section 18. The light path assembly 14 generates and transmits light through the flow cell assembly 12 within the electro-optical section 16 while the air flow control section 18 controls the flow of air outside of the electro-optical section 16 to reduce Schlieren noise. Air flow is also controlled by outer wall 111 and upper wall 112 of cabinet 102 surrounding the apparatus below the level of the air chamber 60.

20 This apparatus 10 has particular application in a micro-liquid chromatograph. Micro-liquid chromatography is a form of high performance liquid chromatography that differs from conventional high performance liquid chromatography in that the inside diameter of the column is substantially less than the usual four to five millimeters.

The flow cell assembly 12 is connected at its top end to a liquid chromatographic column 20 and at its bottom end to an eluate outlet 22. At the upper end of the column 20 is: (1) a sample injection valve 24 for

applying samples to the chromatograph for analysis; and
(2) a high pressure eluant inlet 26 from a source of
eluant which is generally at ambient temperature.

The chromatograph itself may be of any type but the
preferred embodiment is directed to a micro-scale, high
performance liquid chromatograph such as that described
in copending patent application 300,567 filed by Robert
W. Allington on September 9, 1981 and assigned to the
same assignee as this application.

10 The light path assembly 14 includes a deuterium
lamp assembly 30 and an optical compartment 32 mounted
side-by-side so that light from the deuterium lamp
assembly 30 is transmitted to the optical compartment 32
where it is caused to flow through the flow cell
assembly 12 within the optical compartment 32. The
deuterium lamp assembly 30 includes a deuterium lamp 34
and an aspheric condensing mirror 36 which focuses light
through a small slit at 38 into the optical compartment
32.

20 The optical compartment 32 is sealed so that air
from the air flow control section 18 contacts it on its
outer compartment surface but does not flow through the
optical path. It includes an aspheric monochromator
focusing mirror 40, a diffraction grating assembly 42
and a beam splitter 44. The aspheric monochromator

focusing mirror 40 is positioned to receive light from the deuterium lamp assembly 30 after it has passed through the slit at 38 and focuses the light upon the diffraction grating assembly 42.

10 The diffraction grating assembly focuses selected frequencies of light on the beam splitter 44. A portion of the light passing through the beam splitter 44 is transmitted through the flow cell assembly 12 and reflected by the collecting mirror 46 onto a first detector 48 which generates a signal on conductor 50. A second portion of the light from the beam splitter 44 is focused on a second detector 52 resulting in a signal on conductor 54. These signals are used to provide information about the sample as described in the below mentioned patent application and as known in the art.

20 The electro-optical section 16 includes both the deuterium lamp assembly 30 and the optical compartment 32 as well as the electronic equipment necessary for a typical absorbance monitor resulting in output signals that provide information about the eluate flowing through the eluate outlet 22.

 The absorbance monitor in the preferred embodiment is similar to the one disclosed in United States patent application 351,193 filed in the name of Robert W. Allington on February 22, 1982, entitled Absorbance

Monitor and assigned to the same assignee as this application. However, the absorbance monitor has been modified to accommodate the chromatographic column and flow cell within the cabinet in the manner shown in FIG. 1 in the preferred embodiment. The specific absorbance monitor is not part of this invention.

10 The air flow control section 18 includes a blower 56, an air duct 58 and an air chamber 60. The air duct 58 is generally a parallelepiped, being formed of a top and four side walls mounted over an outlet from the cabinet to the electro-optical section 16. The walls are 1/4 inch thick and it has a volume of approximately 0.01 cubic foot with the vertical sides being one and one-quarter inches by one and one-eighth inches and the entire air duct 58 being 11 1/2 inches in height. It is positioned against the air chamber 60 and shares a common top with it.

20 The air chamber 60 encloses the top of the chromatographic column 20, the sample valve 24 and the eluant inlet 26. A connecting wall 62 between the air duct 58 and the air chamber 60 is slightly shorter, forming an open space 68 for communication between the two of approximately one and one-half inches by two inches to permit air to flow from the air duct 58 to the air chamber 60. The volume of the air chamber is

approximately 0.25 cubic foot and its walls are approximately 1/4 inch thick.

To provide air to the air duct 58 and from there to the air chamber 60, the blower 56 is mounted within the electro-optical section 16 and communicates through the top thereof with the bottom of the air duct 58 through an opening 69. It flows approximately 10 cubic feet per minute through the air duct 58 into the air chamber 60. Air from the air chamber 60 flows downwardly over the top portion of the chromatographic column 20 and back into the electro-optical section 16 where it blows across the surface of the optical compartment 32 to remove heat therefrom.

To enable an operator to use the chromatographic column, the walls of the air duct 58 and air chamber 60 are of acrylic plastic and thus transparent. The walls of the air chamber 60 contain a first opening at 64 through which the eluant inlet 26 passes and a second opening 66 through which the sample valve 24 may be manipulated with knob 67. Sample is loaded into the sample valve by injection from a conventional hypodermic needle introduced through hole 65. Excess sample exits the valve through vent tube 63 which passes through hole 61.

In the preferred embodiment, the ratio of the

volume between the air duct 58 and the air chamber 60 is approximately 1 to 25. The ratio of the air duct 58 to the air chamber 60 should be in a range less than a ratio of 1 to 1.5 and more than a ratio of 1 to 300 for efficient operation and the ratio of the air chamber 60 to the volume of the electro-optical section 16 which generates heat should be no greater than 1.5 to 1 and no less than 1 to 30.

10 The volumetric flow rate caused by the blower 56 should be sufficient to create enough static pressure to force air to circulate and reach equilibrium in a reasonable amount of time. More importantly, it is necessary that the equilibrium temperature distribution and thermal fluxes must meet specific criteria which will be described later, in order to accomplish the objects of the invention. In the preferred embodiment the blower 56 exchanges about 10 cubic feet of air per minute and should have a capacity to change at least one-tenth of the volumetric amount of air in the air
20 chamber 60 and air duct 58 each minute.

While a blower is used in the preferred embodiment, any other technique for causing air to circulate could be used instead. For example, a heater located at 69 can be used to cause air to be heated and rise.

While the blower 56 is an effective means for

starting recirculation and quickly reaching equilibrium, it may be turned off and recirculation, once started, will continue. This circulation of air occurs because air from a warmer part of the electro-optical section 16 rises and flows through the opening 69 upwards into the vertical duct 58, through opening 68 and over into the compartment 60 where it cools. As it cools, it falls because it becomes more dense than the warmer air rising in the air duct 58; it pulls downwardly to pull air up through the air duct 58 and over through the opening 68. The falling air in compartment 60 re-enters the electro-optical section, downwards through the opening in the cabinet 102 that surrounds the chromatographic column 20. This part of the cabinet 102 is cooler and the air inside is more dense than in the part of the cabinet under the opening 69, so air rises out of opening 69 and falls back into the cabinet through the cabinet opening around column 20. In this manner, air flow continues and thermal equilibrium is maintained although the air flow may be lower and may be in the range of 0.001 the volume of the air chamber each minute rather than being at least equal to the volume of the air chamber each minute.

In operation, the electro-optical section 16 is operated until temperature equilibrium is reached while

the blower 56 is operated. Temperature or heat equilibrium is a condition in which the temperature does not vary more than 0.1 degree Celsius at any location within a one minute period of time. In this condition air flows from the electro-optical section 16 through the air duct 58 into the air chamber 60 through an opening 68 downwardly to the bottom of the air chamber 60 and over the surface of the optical compartment 32 back into the electro-optical section 16 for recirculation.

10 In the preferred embodiment, it requires three hours from cold start or one hour from a standby warm-up start to reach equilibrium but this is a function of the volume of air, the amount of localized heat released and the rate of amount of air. The air blower may be any suitable commercial unit such as one having a squirrel cage wheel inside a snail housing driven at approximately 2500 RPM by any suitable motor, which may be operated on 25 volts at about 60 milliamperes from a low-voltage DC supply.

20 Air flow through the air control section 18 while the blower 56 is operating is approximately 10 CFM (cubic feet per minute), at 0.08 inch static pressure. Generally, the chromatograph is not operated until the temperature has stabilized and at this time there is a change in temperature of the air from the blower 56 to

the top of the air duct 58 and as the air drops downwardly from the air chamber 60 to the optical compartment 32 it loses heat to establish an air temperature gradient along the flow path and becomes cooler as it follows that flow path.

10 The fluid in the flow path traveling along column 20 in the same direction as the heated air driven by fan 56 is pre-heated at the top of the flow path and rises in temperature as it flows along. However, at a distance of about 10 to 20 centimeters above the flow cell, the air has cooled to about the temperature of the fluid in the flow path because the air flow is constantly losing heat to the outside environment through the nearest walls of the air chamber. When the air cools sufficiently, it no longer heats the fluid in the flow path and the temperature of the fluid in the flow path does not change as it flows downwardly from this point.

20 As the fluid in the column 20 flows down to and inside the light path compartment 14, it starts to pick up heat by thermal conduction from the optical compartment 32 which in turn is being heated by thermal conduction from the electro-optical section 16. At the same time, the air flow continues down around the lower part of the column 20 and around the walls of the

optical compartment 32. All this time, the flowing air is still losing heat to the outside environment first through the outer walls of the air chamber 18 and then through outer wall 111 and upper wall 112 of cabinet 102 surrounding the light path assembly 14. The air continues to cool and continues dropping through lower and lower temperatures which are colder than the lower part of the column 20 and the flow cell 12.

10 The air flow rate and sizes and spacings of the components are such that the thermal equilibrium temperatures of the flowing liquid in the lower part of the column 20 and in the flow cell 12 are equal. This is because at this particular temperature, along all or most of this part of the flow path, the heat lost to the air equals the heat gained by conduction from the electro-optical section 16. The positive and negative heat fluxes are higher near the flow cell 12 than at the lower 10 to 20 centimeters of the column 20 but in both places, the positive and negative heat fluxes
20 external to the flow path are equal for the same temperature inside the flow path.

It is believed that this result can only be obtained using the form of co-current flow heat exchanger described. This is a surprising result as counter-current flow heat exchangers are universally believed to

be more efficient than co-current heat exchangers. In fact, co-current heat exchangers are commonly believed to be the least efficient of all forms of heat exchangers.

10 When the temperature has stabilized, the chromatograph quickly may be operated so its samples are injected in the sample injection valve 24 while eluant flows through the inlet 26 and downwardly in the column 20 in the same direction as the air flow. As the mobile phase flows downwardly, it is heated to a temperature closer to that within the electro-optical section 16 and thus that of the optical compartment 32 and the flow cell 12.

Heat is transferred into the flow cell 12 by conductance from the electro-optical section 16 but a portion of this heat is absorbed by the air as it flows downwardly around the surface of the optical compartment 32 and back into the electro-optical section 16.

20 Because additional heat conducted to the optical compartment 32 from the electro-optical section 16 is differentially offset by the increased heat from hotter air flowing through the air duct 58 and the air chamber 60, the equipment is not sensitive to changes once it has stabilized. Thus an increase in heat conducted into the optical compartment 32 is accompanied by an increase

in heat convected into the air chamber 60 and the two temperatures stay in balance.

The two temperatures stay in balance because the heat loss of the air through the air chamber walls from the air flowing downwardly through the air chamber maintains itself in the same proportionate increase as the heat lost from the area of the flow cell 12 in the optical unit 32 to the surrounding environment. This balance is maintained because more heat is removed from the area of the flow cell 12 to compensate for an increase in loss through the chamber walls from the air and this maintains stability. Conversely, changes in ambient temperature also have small effect in changing the differential temperature between the flow cell 12 and the column 20 when this differential is initially set to zero by use of the thermal system described herein because reductions in heat loss from the air flowing through the chamber are offset by reductions from the area of the flow cell 12.

Because of the automatic balancing of heat losses, the manual adjustment of the speed of the blower 56 is relatively easily made to obtain stability with a slight difference in temperature between the flow cell 12 and the fluid in the column 20 flowing through the flow cell 12. It is possible to maintain that diffe-

rence to a value of less than one degree Celsius.

In FIG. 2 there is shown a schematic diagram of the optical compartment 32, the deuterium lamp compartment 30 and a blower control system 70. In one embodiment, the blower control system 70 aids in stabilizing the temperature within the optical compartment to reduce Schlieren noise caused by temperature gradients from heat generated in the deuterium lamp compartment and electro-optical section.

10 To detect chromatographic peaks, the entrance aperture plate or slot 38 of the optical compartment 32 is positioned between the optical compartment 32 and the deuterium lamp compartment 30 so that light from the deuterium lamp 34 is condensed onto the aperture by the mirror 36 and passes from there into the optical compartment 32 which is next to it. Electrical signals from the optical compartment 32 are conducted outwardly from conductors 50, 54 and 72 with the signal from the
20 conductors 50 and 54 being conducted to the absorbance detector disclosed in the aforementioned patent application and signals from the conductor 72 being conducted to the blower control system 70.

The optical compartment 32 is positioned in the path of air flowing downwardly from the air chamber 60 to be cooled thereby. Within this unit, a small amount

of heat may be generated from a tungsten lamp (not shown) which may be used as an alternate source of light to the deuterium lamp 34.

10 The grating 42 is pivotable to select frequencies of light from either the tungsten lamp or the deuterium lamp 34. This selected frequency of light is transmitted to the beam splitter 44. The beam splitter 44 transmits light in one beam through the flow cell 12 and in another beam to the detector 52. The light flowing through the flow cell 12 is reflected from the collecting mirror 46 onto the detector 48 with the conductors 50 and 54 respectively conducting signals from the detectors 48 and 52.

20 The apparatus and method of reducing Schlieren noise: (1) produces and stabilizes a temperature gradient of downwardly decreasing temperatures in the air circulating through the system to reduce temperature variations in the column by opposing the downwardly-increasing fluid temperature gradient that would otherwise occur; (2) reduces temperature changes between the various portions of the eluant flowing from the column 20, through the upper part of the flow cell 12, and through the light path of the flow cell, due to an imbalance of net transverse thermal flux at any point along this entire part of the chromatographic flow path

to reduce any Schlieren noise; and (3) reduces temperature changes in the air within the optical compartment to reduce extra-flow cell Schlieren noise caused by different density layers of air. The principal effect, however, is noise caused by the fluid flowing through the flow cell 12.

10 Generally, after the warming up of the light source, the light intensity variations sources in the short term are less low. The variation in light intensity after this warm-up period is less than ten percent within one minute. The absorbance measurements are made more accurately than this so, therefore, it usually requires recourse to a reference photocell or feedback stabilization of the light source in one of the ways known in the art. The frequencies of light which are selected for transmission fall within the range of 180 to 3,000 nanometers.

20 To adjust the rate of flow of air from the blower 56, the blower control system 70 includes a differential amplifier 78, a power amplifier 80, a switch 82 and the motor 84 for the blower 56. A first temperature measuring device 76 is preferably mounted on the chromatographic column above the flow cell and a second temperature measuring device 86 is mounted within the optical compartment 32, preferably on the flow cell 12

proximate to its light path and connected through conductor 72 to one input of the differential amplifier 78, the other input of which is electrically connected to the temperature measuring device 76, located outside the optical compartment 32 which is the temperature of the eluant in the column 20 (FIG. 1).

10 With this arrangement, the signals from the temperature measuring devices 76 and 86 are compared in the differential amplifier 78. One input of the differential amplifier 78 is adjustable by a variable resistance 88 connected in circuit with one of the temperature measuring devices 76 and the differential amplifier 78. The temperature measuring device 76 is positioned at a location where it measures column temperature or ambient temperature such as being spaced by insulation or physically spaced from the electro-optical section 16.

20 To select manual adjustment of the air movement or automatic adjustment, the switch 82 is a single pole, double-throw switch having its switch arm electrically connected to the input of the blower motor 84. One of the contacts against which it may be thrown is connected to the output of the power amplifier 80, the input of which is electrically connected to the output of the differential amplifier 78.

When the switch 82 is connected to the output of the power amplifier, variations from a set point, controlled by the variable resistor 88, cause changes in the speed of the motor 84 and thus increasing stability in temperature. When the walls of the light path of the flow cell are at the same temperature as the eluate entering the flow cell, Schlieren noise is substantially reduced because there are little changes in the density of strata of liquid to cause changes in the refraction of light passing through the flow cell 12.

In the preferred embodiment, because of the ease of obtaining stability with the method and apparatus for reducing Schlieren noise in a liquid chromatograph, the speed of the blower 56 is only controlled manually and changed very infrequently. After air flow has been achieved, it may be turned off altogether. This may be accomplished in the illustrative embodiment of FIG. 2 by throwing the switch 82 against a second contact connected to a source of potential 90 through a variable resistor 92. The resistance of the variable resistor 92 and thus the blower speed may be adjusted manually from outside of the cabinet through a control knob 94.

With this arrangement, the speed of the blower 56 may be adjusted from the control knob 94 while measuring temperature within the optical compartment 32 or the

electro-optical section 16 (FIG. 1) until temperature stability is obtained. By proper sizing of the blower and its motor, the control may be eliminated altogether. Any suitable blower may be used such as, for example, a blower snail equipped with a blower wheel rotated at a fixed speed of 2440 RPM by a motor producing 10 CFM at 0.08 sp. Standard commercial units have provided essentially Schlieren noise-free operation of variable wavelength HPLC detectors equipped with a 5 millimeter length by 0.25 millimeter diameter light path flow cell and the air chamber and other modifications described herein.

In FIG. 3 there is shown a perspective view of the apparatus for reducing Schlieren noise 10 having the air flow control section 18 and the electro-optical section 16 showing the circuitry therein. As best shown in this view, the chromatographic column 20 is mounted to an adjustable arm 100 which may be positioned along a support column 103 which it grips at a fixed location upon tightening of the knob 104.

The arm 100 and support column 103 are enclosed within the air chamber 60 to support the column 20 therein at a fixed height which may be adapted in the preferred embodiment to either 10 centimeter or 25 centimeter columns. With this arrangement, the top of

the columns and the sample injection valves may be mounted within the air chamber 60 and controlled by blowing air through the air duct 58 into the air chamber 60 until stability is reached and Schlieren noise reduced. The arm 100 and support column 103 are rigid and rigidly mounted to the frame of the housing. They are made of thermally conductive material to permit easy heat transfer and avoid the establishment of undesirable heat gradients.

10 From the above description, it can be understood that the apparatus and method for reducing Schlieren noise in a liquid chromatograph has several advantages, such as: (1) it is inexpensive; (2) it aids in providing temperature stability; (3) it is easy to control; (4) it stabilizes within a relatively short period of time; (5) it aids in the reduction in temperature-dependent retention time changes; (6) it greatly reduces Schlieren noise without degrading resolution; and (7) it

20 Although in the preferred embodiment the air blows to the top of the air chamber 60 through a vertical air duct 58, it is only necessary for the air to be warmer as it moves along the column and cooler against the flow cell to equalize temperatures. Moreover, the column may be mounted in many different ways and at different

elevations with respect to the cabinet.

Although a preferred embodiment of the invention has been described with some particularity, many modifications and variations in the preferred embodiment are possible without deviating from the invention. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be practiced other than as specifically described.

-A-

CLAIMS

1. A method of operating a liquid chromatograph having a least a chromatographic column (20), a sample injection valve (24), and a flow cell comprising the steps of applying electrical power to an absorbance detector (16) within an enclosure (32) containing at least the flow cell and a portion of the chromatographic column (20); characterized by causing air to flow from the enclosure (32) into an air chamber (60) that encloses a sample injection valve (24) and at least a part of a chromatographic column (20) and recirculating the air from a location near the sample injection valve (24) along the column (20) toward the flow cell (12) until temperature changes with respect to time at each location are within less than 0.1 degree Celsius within the enclosure and chamber within a one minute time period; passing eluant after the temperature has stabilized through the column (20) and flow cell (12); transmitting a beam of light having a wave length within a range of wave lengths of 180 nanometers to 3,000 nanometers through the flow cell (12) from a source of light that varies less than ten percent in intensity in a one minute period; and detecting changes in the absorbance of light through said

flow cell (12), with the air flow being caused initially by blowing air from the enclosure (32) to the inlet of the chromatographic column and back to the enclosure (32) at a rate in the range of 1 to 100 volumes of air per minute for each volume of capacity of the chamber (60) and discontinuing the blowing of air after the temperature has stabilized and permitting it to flow at a rate of at least .001 volume of air per minute for each volume of capacity of the air chamber (60).

2. A method of operating a liquid chromatograph according to claim 1 characterized by the steps of causing air to flow along a chromatographic column (20) from an electro-optical enclosure (32) and back to the enclosure (32) in the same direction the eluant flows in the column (20); and after temperature has stabilized with respect to time in the enclosure, performing chromatographic runs.


3. A method according to either claim 1 or 2 characterized in that the step of causing air to flow includes the step of causing air to flow from the enclosure (32) into an air chamber (60) having at least a part of a chromatographic column (20) within it and recirculating the air from a point on the column (20)

3-

spaced away from its end closer to the flow cell (16) into juxtaposition with the flow cell (12) until the temperature has stabilized within the air chamber (60); and transmitting eluant through the column (20) and flow cell (12) after the temperature has stabilized.

4. A method according to any of claims 1-3 further characterized in that the step of causing the air to flow includes the step of causing air to flow from the enclosure (32) into an air chamber (60) and recirculating the air until the temperature changes with respect to time at each location are within less than 0.1 degree Celsius per minute within the air chamber (60).







Europäisches Patentamt
European Patent Office
Office européen des brevets

Publication number:

0 164 080
A3

EUROPEAN PATENT APPLICATION

Application number: **85106717.3**

Int. Cl.³: **G 01 N 30/74**
G 01 N 21/03

Date of filing: **31.05.85**

Priority: **06.06.84 US 617700**

Date of publication of application:
11.12.85 Bulletin 85/50

Date of deferred publication of search report: **07.12.88**

Designated Contracting States:
DE FR GB

Applicant: **ISCO, Inc.**
4700 Superior Street
Lincoln Nebraska 68504(US)

Inventor: **Allington, Robert William**
2030 Euclid
Lincoln Nebraska 68502(US)

Representative: **UEXKÜLL & STOLBERG Patentanwälte**
Börsenstraße 4
D-2000 Hamburg 52(DE)

Method and apparatus for reducing schlieren noise in a liquid chromatograph.

A beam of light falling within the range of 180 to 3,000 nanometers is transmitted through a flow cell (12) in an optical compartment of an absorbance detector (16) after warm up of the equipment while the eluant flows through the flow cell (12) from a chromatographic column (20). The column extends upwardly from the absorbance detector (16) into an air chamber (60) having a volume of approximately 0.25 cubic foot formed with acrylic walls. Air flows from the absorbance detector (16) under the power of a fan at approximately 10 cubic feet per minute upwardly through an air duct having a cross section of approximately 1.5 square inches to the top where it connects with the air chamber (60), the speed of the motor being adjustable until temperature varies less than one degree Celsius between the flow cell (12) and the lower 10 centimeters of the column. Under these conditions Schlieren noise from the flow cell (12) due to flow-induced thermo-optical effects is reduced.




Fig. 1



European Patent
Office

EUROPEAN SEARCH REPORT

0164080

Application Number

EP 85 10 6717

| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|---|---|---|---|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int. Cl.4) |
| X, P | EP-A-0 139 929 (ISCO INC.) * Pages 4-6, 9, 12-19, 23, 28-33 * | 1-3 | G 01 N 30/74 G 01 N 21/03 |
| | | | TECHNICAL FIELDS SEARCHED (Int. Cl.4) G 01 N 30/74 G 01 N 21/15 G 01 N 30/36 B 01 L 7/02 G 01 N 30/30 |
| The present search report has been drawn up for all claims | | | |
| Place of search THE HAGUE | | Date of completion of the search 25-09-1988 | Examiner BOEHM CH.E.D. |
| CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document | | | |

EPO FORM 1500 (2.1) (P0401)